


NPN 500mA 40V Digital Transistors (Bias Resistor Built-in Transistors)

Parameter	Value	
V_{CEO}	40V	
I _C	500mA	
R	2.2kΩ	



● Features

- 1) Built-In Biasing Resistors
- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors (see inner circuit).
- 3) The bias resistors consist of thin-film resistors with complete isolation to allow negative biasing of the input. They also have the advantage of completely eliminating parasitic effects.
- 4) Only the on/off conditions need to be set for operation, making the circuit design easy.
- 5) Complementary PNP Types :DTB123TK
- 6) Lead Free/RoHS Compliant.

Application

Switching circuit, Inverter circuit, Interface circuit, Driver circuit

Packaging specifications

Part No.	Package	Package size	Taping code	Reel size (mm)	Tape width (mm)	ordering	Marking
DTD123TK	SMT3	(mm) 2928	T146	180	8	unit (pcs) 3,000	F02

Outline

● **Absolute maximum ratings** (Ta = 25°C)

Parameter	Symbol	Values	Unit
Collector-base voltage	V _{CBO}	50	V
Collector-emitter voltage	V _{CEO}	40	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I _C	500	mA
Power dissipation	P _d *2	200	mW
Junction temperature	T _j	150	°C
Range of storage temperature	T _{stg}	-55 to +150	°C

●Electrical characteristics(Ta = 25°C)

Parameter	Symbol	Conditions	Min.	Тур.	Max.	Unit
Collector-base breakdown voltage	BV_CBO	I _C = 50μA	50	-	-	V
Collector-emitter breakdown voltage	BV _{CEO}	I _C = 1mA	40	-	-	V
Emitter-base breakdown voltage	BV_{EBO}	I _E = 50μA	5	-	-	V
Collector cut-off current	I _{CBO}	V _{CB} = 50V	1	-	0.5	μΑ
Emitter cut-off current	I _{EBO}	V _{EB} = 4V	1	-	0.5	μΑ
Collector-emitter saturation voltage	V _{CE(sat)}	$I_{C} / I_{B} = 50 \text{mA} / 2.5 \text{mA}$	1	-	0.3	V
DC current gain	h _{FE}	V_{CE} = 5V , I_{C} = 50mA	100	250	600	-
Emitter-base resistance	R	-	1.54	2.2	2.86	kΩ
Transition frequency	f _T *1	$V_{CE} = 10V, I_{E} = -50mA,$ f = 100MHz	ı	200	-	MHz

^{*1} Characteristics of built-in transistor

^{*2} Each terminal mounted on a reference footprint

●Electrical characteristic curves(Ta = 25°C)

characteristics

10 $V_{CE}=5V$ $V_{CE}=5$

Fig.1 Grounded emitter propagation

Fig.2 Grounded emitter output characteristics $I_i =$ 500 5.0mA Ta=25°C 4.5mA COLLECTOR CURRENT : I_C (mA) 4.0mA 400 3.5mA 3.0mA 300 2.5mA 2.0mA 200 1.5mA 1.0mA 100 0.5mA 0 0A 0 5 10 **COLLECTOR TO EMITTER** VOLTAGE: V_{CE} (V)

Fig.3 DC Current gain vs. Collector Current 1k V_{CE}=5V 500 DC CURRENT GAIN: hFE 200 100 Ta= 100°C 25°C 50 -40°C 20 10 2 20 50 100 200 0.5

COLLECTOR CURRENT: I_C (mA)


vs. Collector Current $I_{\rm C}/I_{\rm B}=20$ 500m Ta= 100°C 200m COLLECTOR SATURATION 25°C VOLTAGE: V_{CE}(sat) (V) -40°C 100m 50m 20m 10m 5m 2m 1m ∐ 0.5

COLLECTOR CURRENT : I_C (mA)

Fig.4 Collector-emitter saturation voltage

●Dimensions (Unit:mm)

SMT3



Patterm of terminal position areas

DIM	MILIM	ETERS	INCHES		
DIM	MIN	MAX	MIN	MAX	
Α	1.00	1.30	-	0.051	
A1	0.00	0.10	0	0.004	
A3	0.25		0.01		
b	0.35	0.50	0.014	0.02	
С	0.09	0.25	0.004	0.01	
D	2.80	3.00	0.11	0.118	
E	1.50	1.80	0.059	0.071	
е	0.95		0.0	04	
HE	2.60	3.00	0.102	0.118	
L1	0.30	0.60	0.012	0.024	
Lp	0.40	0.70	0.016	0.028	
Q	0.20	0.30	0.008	0.012	
х	_	0.10	_	0.004	
у	_	0.10	_	0.004	

DIM	MILIMI	ETERS	INCHES		
DIM	MIN MAX		MIN	MAX	
e1	2.	2.10		08	
b2		0.60	-	0.024	
11	-	0.90	-	0.035	

Dimension in mm/inches

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ROHM Semiconductor: DTD123TKT146